

SPECIALITY MIRRORS

FOOD PROCESSING:

- Ranges conform to food industry standards.
- Stainless Steel or Acrylic face allows hygienic cleaning.
- Stainless Steel 'J' arm adjustable mounting bracket.
- Orange vinyl trim for high visibility in factory settings.

FORK LIFT REAR VIEW:

- 180° view significantly reduces blind spots.
- Shatter resistant acrylic face.
- Integral fixing bracket.

TRAFFIC MIRRORS:

- Allows maximum visibility at crossroads, intersections and other areas of restricted view.
- Supplied with red reflective strips and a 75mm pole clamp bracket.
- Wall mounting plate available (see fixings).

ANTI-VANDALISM:

- Manufactured from highly polished mirror-quality stainless steel.
- Unbreakable, heat resistant and easy to maintain.
- Ideal for use in subways, multi-story car parks.



Food Processing



Traffic Mirror



Anti-Vandalism Rectangular

FOOD PROCESSING ACRYLIC

Model	Description (mm)	Viewing Distance (M)	Face Thickness (mm)	Back
M18244V	450 diameter	7	2	Moulded ASA Vinyl
M18266V	600 diameter	10	2	Moulded ASA Vinyl
M18287V	800 diameter	14	3	Moulded ASA Vinyl

Supplied with bright zinc 'J' arm bracket

FOOD PROCESSING STAINLESS STEEL

Model	Description (mm)	Viewing Distance (M)	Face Thickness (mm)	Back
M16144FE	450 diameter	7	0.7	Stainless Steel
M16166FE	600 diameter	10	0.9	Stainless Steel
M16187FE	800 diameter	14	0.9	Stainless Steel

Supplied with bright zinc 'J' arm bracket

FORK LIFT REAR VIEW

Model	Description (mm)	Viewing Distance (M)	Acrylic Face Thickness (mm)	Back
M19952A	300 x 150 half face	12	2	Moulded ASA Vinyl
M19952T	300 x 150 half face	12	2	-

TRAFFIC MIRRORS

Model	Description (mm)	Viewing Distance (M)	Acrylic Face Thickness (mm)	Back
M18666CS	600 diameter	38	2	Moulded ASA Vinyl
M18687CS	800 diameter	46	2	Moulded ASA Vinyl
M18642R	600 x 400 rectangular	38	2	Moulded ASA Vinyl

Supplied with 75mm diameter pole mounting brackets

ANTI-VANDALISM STAINLESS STEEL

Model	Description (mm)	Viewing Distance (M)	Face Thickness (mm)	Back
M500CD	500 ceiling dome	5	1.2	-
M16047C ¹	450 diameter	32	0.7	Powder Coated Steel
M16066C ²	600 diameter	42	0.7	Powder Coated Steel
M16336C ²	320 x 225 rectangular	23	0.7	Stainless Steel
M16505W	500 wall dome	30	0.9	-
M16525HL	250 x 250 quarter face	5	1.2	-
M16529HL	500 x 250 half face	8	1.2	-

¹Supplied with wall and 75mm diameter pole mounting brackets.

²Supplied with 32mm diameter pole clamp bracket only.

Viewing Distance:

This is the combined distance from the observer to the mirror PLUS the distance from the mirror to the object being observed.