

DEPOSIT SAFES

In most commercial environments there is a need for a deposit safe, somewhere where you can safely deposit items such as cash, keys and other valuables without the need for keys and codes to open the safe and without drawing attention to its existence. Securikey provides a wide range of quality deposit safes, with a variety of cash ratings and deposit methods, which offer total flexibility in the workplace.

MINI VAULT SILVER (SEE PAGE 18):

- Ideal under desks or counters.
- Available with letter slot deposit (Mini Vault 1) or front hopper deposit (Mini Vault 2).

EURO GRADE (SEE PAGES 20):


- A wide range of models suitable for most applications.
- A choice of 3 different deposit methods including rotary drum, letter slot or capsule deposit tube.
- The secondary installation of a rotary drum or capsule deposit requires removal of the VdS badge. Please inform your insurers accordingly.

UNDERFLOOR SAFES (SEE PAGE 27):

- Ideal for use where space is at a premium.
- Deposit tube diameter is 52mm.

STEEL STOR (SEE PAGE 30):

- SCDR48 offers a top loading rotary deposit drum with a 90mm x 250mm aperture. A spring return ensures the drum is always closed.
- SC60 and SC100 can be supplied with a front loading rotary drum deposit, having an aperture of 90mm x 200mm x 220mm.
- SC60WDD is equipped with a lockable front deposit drawer thus removing the need to open the cabinet. It features a 240mm x 160mm x 75mm drawer aperture.



Rotary Drum



Mini Vault 2 Deposit



SC60WDD

UNDERFLOOR SAFES

Model	External Dimensions (mm)			Weight (kg)
	Height ¹	Width	Depth	
Housesafe Extra Deposit	305	305	305	24
Protector 3 Deposit Body	320	360	270	18.5
Protector 5 Deposit Body	410	360	270	20.5

¹ Excludes neck.

MINI VAULT SILVER

Model	External Dimensions (mm)			Internal Dimensions (mm)			Aperture Size (mm)		Weight (kg)	Volume (l)
	Height	Width	Depth	Height	Width	Depth	Height	Width		
Mini Vault 1 Deposit	294	374	325	210	365	260	20	140	31	15
Mini Vault 2 Deposit	532	374	425	260	365	360	100	250	57	34

Deposit models and modifications can result in reduced cash ratings. Please check with your insurers.

STEEL STOR

Model	External Dimensions (mm)			Weight (kg)
	Height	Width	Depth	
SCDR48	480	320	320	42
SC60WDD*	760	540	400	110

*Supplied with 1 shelf and 2 door boxes.

EURO GRADE

Model	Aperture Size		
	Height	Width	Depth
Rotary Drum	90	200	220
Slot Deposit	To customer specification		
Tube Deposit	To customer specification		

ALTERNATIVE LOCKING OPTION AVAILABLE – SEE PAGE 5