





EN1143-1 Burglary protection



Grade I







Class I E



4102 (light fire protection)



Domestic insurable up to EUR 65.000



Commercial insurable up to EUR 20.000

[Safes] [Type AG]

A distinctive feature of the AG series safes is their slim design. An external width of just 450 mm thanks to their space-saving wall construction allows an optimal utilisation with room for 5 file folders side by side (from AG10 up).

[Product information]

DIN right - model designation R Hinge

option: DIN left

Door opening angle 180°

double-walled, filled with high resistant barrier material Body

triple-walled, filled with high resistant barrier material, internal boltwork Door structure

protected by sheets of hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

prepared for floor and rear wall anchoring Anchoring

anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

model designation K - double-bit lock VdS class 1, Cawi 2 keys (95 mm) Lock

model designation E - electronic lock VdS class 2, M-Locks EM3520

option: other lock models

shelf (adjustable from AG10 up, height setting 85 mm) Equipment

option: key rack (with option inspection window from AG 20 up)

option (from AG10 up): additional shelf, inside locker, drawer, pull-out shelf

option: certified steel plinth to raise the level of the safe, Accessories

fire protection door rebate seals, interior lighting,

inspection window in boltwork door cover (from AG10 up)

[Equipment options] **Outside dimensions** Inside dimensions Volume Weight



